


Solenoid valve MC-2-1/8

Part number: 2187

FESTO



Data sheet

Feature	Value
Valve function	2/2-way, single solenoid, closed
Type of actuation	Electrical
Standard nominal flow rate (standardised to DIN 1343)	300 l/min
pneumatic working port	G1/8
Operating pressure	-0.095 MPa...0.7 MPa -0.95 bar...7 bar
Design	Poppet valve with spring return
Type of reset	Mechanical spring
Degree of protection	IP65
Nominal size	4 mm
Sealing principle	Soft
Manual override	None
Type of piloting	Direct
Flow direction	Non-reversible
Switching time off	20 ms
Switching time on	18 ms
Duty cycle	100%
Characteristic coil data	110 V AC: 50/60 Hz, pick-up power 30.0 VA, holding power 22.0 VA 110 V DC: 12.7 W 120 V AC: 60 Hz, pick-up power 30.0 VA, holding power 22.0 VA 12 V AC: 50 Hz, pick-up power 30.0 VA, holding power 22.0 VA 12 V DC: 11.7 W 220 V AC: 50/60 Hz, pick-up power 30.0 VA, holding power 22.0 VA 220 V DC: 15.0 W 240 V AC: 50 Hz, pick-up power 30.0 VA, holding power 22.0 VA 240 V DC: 17.9 W 24 V AC: 50 Hz, pick-up power 30.0 VA, holding power 22.0 VA 24 V DC: 11.0 W 380 V AC: 50/60 Hz, pick-up power 30.0 VA, holding power 22.0 VA 42 V AC: 50/60 Hz, pick-up power 30.0 VA, holding power 22.0 VA 42 V DC: 12.0 W 48 V AC: 50 Hz, pick-up power 30.0 VA, holding power 22.0 VA 96 V DC: 11.0 W
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
LABS (PWIS) conformity	VDMA24364-C1-L
Storage temperature	-40 °C...100 °C

Feature	Value
Media temperature	-10 °C...60 °C
Ambient temperature	-5 °C...40 °C
Type of mounting	With through-hole
Pneumatic connection, port 1	G1/8
Pneumatic connection, port 2	G1/8
Note on materials	RoHS compliant